



Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

1 Identification

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

Other Means of Identification: Mixture

Other Name: Mars™, Mars™ HNRC, Marc™ HCAC, Mars™ Healthcare, Cleanroom, Millennia®.

Recommended Use of the Chemical and Restriction on Use: Ceiling tiles for interior use.

Details of Manufacturer or Importer:

USG Boral Building Products Pty Limited (ACN 004 231 976)
251 Salmon Street
Port Melbourne VIC 3207

Phone Number: 1800 811 222

Emergency telephone number: National Poison Information Centre: 13 11 26

2 Hazard(s) Identification

Hazardous Nature:

Not classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

The product is not classified, according to the Globally Harmonised System (GHS).

Signal Word None

Hazard Statements None

Precautionary Statements None

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 1332-58-7	Kaolin	<10%
CAS: 9005-25-8	Starch	<5%
CAS: 471-34-1	Calcium carbonate	<2%
CAS: 21645-51-2	Aluminium hydroxide	<2%
CAS: 1317-65-3	Limestone	<2%

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin irritation, remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Do not rub eyes. Seek medical attention if symptoms occur.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

(Contd. of page 1)

Ingestion:

If swallowed, do not induce vomiting. Rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek medical attention if symptoms occur.

Symptoms Caused by Exposure:

Inhalation: Dusts may cause respiratory irritation.

Skin Contact: Dusts may cause mechanical skin irritation.

Eye Contact: Dusts may cause mechanical eye irritation.

Ingestion: Dusts may cause gastrointestinal irritation.

5 Fire Fighting Measures

Suitable Extinguishing Media: Use fire extinguishing methods suitable to surrounding conditions.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon.

This product is not flammable, but may burn or decompose in a fire.

Product close to fire should be removed if safe to do so.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved class P1 (particulate) respirator, protective gloves and eye or face protectors for protection against dust. Evacuate all non-essential personnel from affected area. Do not breathe dust. Ensure adequate ventilation. Avoid generating dust.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Clean the area using a HEPA vacuum cleaner. Wet mopping and wiping is acceptable if vacuuming is not workable. Do not use compressed air.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended when cutting the product to avoid eye or skin contact and inhalation of dust. In order to minimise dust generation when cutting the product hand tools are recommended in preference to power tools. If power tools are used, these should be fitted with dust extraction or other effective local ventilation. Always wash hands after use.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Protect from high humidity, excessive moisture and physical damage. Keep away from strong oxidising agents.

8 Exposure Controls and Personal Protection

Exposure Standards:

CAS: 1332-58-7 Kaolin

NES	TWA: 10 mg/m ³
-----	---------------------------

WES	TWA: 10 mg/m ³
-----	---------------------------

CAS: 9005-25-8 Starch

NES	TWA: 10 mg/m ³
-----	---------------------------

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

(Contd. of page 2)

WES	TWA: 10 mg/m ³
CAS: 471-34-1 Calcium carbonate	
WES	TWA: 10 mg/m ³
CAS: 21645-51-2 Aluminium hydroxide	
NES	TWA: 2 mg/m ³ as Al
WES	TWA: 2 mg/m ³ as Al
CAS: 1317-65-3 Limestone	
WES	TWA: 10 mg/m ³ As calcium carbonate

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Where an inhalation risk exists, wear a Class P1 (particulate) respirator. See Australian/New Zealand Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Protective gloves are recommended for prolonged contact. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against dust. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form:	Solid
Colour:	White or coloured surface with beige / grey core.
Odour:	Odourless
Odour Threshold:	No information available
pH-Value:	9
Melting point/freezing point:	1,204 °C
Initial Boiling Point/Boiling Range:	Not applicable
Flash Point:	Not applicable
Flammability:	Product is not flammable.
Auto-ignition Temperature:	Not applicable
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	Not applicable
Upper:	Not applicable
Vapour Pressure:	Not applicable
Bulk Density at 20 °C:	240 - 352 kg/m ³
Relative Density:	0.24 - 0.35
Vapour Density:	Not applicable.
Evaporation Rate:	Not applicable
Solubility in Water:	Very low.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

(Contd. of page 3)

Partition Coefficient (n-octanol/water): No information available**Viscosity:** Not applicable

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.**Chemical Stability:** Stable at ambient temperature and under normal conditions of use.**Conditions to Avoid:** No further relevant information available.**Incompatible Materials:** Strong oxidising agents.**Hazardous Decomposition Products:** No hazardous decomposition products known.

11 Toxicological Information

Toxicity:**LD₅₀/LC₅₀ Values Relevant for Classification:****CAS: 1332-58-7 Kaolin**Oral LD₅₀ >5,000 mg/kg (rat)**CAS: 471-34-1 Calcium carbonate**Oral LD₅₀ 6,450 mg/kg (rat)**Acute Health Effects****Inhalation:** Dusts may cause respiratory irritation.**Skin:** Dusts may cause mechanical skin irritation.**Eye:** Dusts may cause mechanical eye irritation.**Ingestion:** Dusts may cause gastrointestinal irritation.**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Based on classification principles, the classification criteria are not met.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:** This product does NOT contain any IARC listed chemicals.**Reproductive Toxicity:** Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:**

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** Prolonged contact may cause skin irritation.**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

(Contd. of page 4)

12 Ecological Information

Ecotoxicity:**Aquatic toxicity:****CAS: 471-34-1 Calcium carbonate**LC₅₀/96 h >56,000 mg/l (mosquito fish)**Persistence and Degradability:** No further relevant information available.**Bioaccumulative Potential:** Bioaccumulation is not expected to occur.**Mobility in Soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulated**Proper Shipping Name** Not regulated**Dangerous Goods Class** Not regulated**Packing Group:** Not regulated

15 Regulatory Information

Australian Inventory of Chemical Substances: All ingredients are listed.**Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:**

Not Scheduled.

16 Other Information

Date of Preparation or Last Revision: 26.11.2019**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au**Abbreviations and acronyms:**

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC₅₀: Lethal concentration, 50 percentLD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Data altered compared to the previous version: Section 1: Other Names**Disclaimer**

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. USG Boral Building Products Pty Limited makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 26.11.2019

Revision: 26.11.2019

Product Name: ECLIPSE™ ACOUSTICAL CEILING PANELS

(Contd. of page 5)

Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.