
Pallet Packing Label Instructions

Stacking Instructions

- Stack tiles or panels on 1200mm x 1200mm shipping pallets. Stack tiles or panels no higher than 1200mm
- Place USG Pallet Packing Label on 2 of 4 faces of pallet so that these labels are clearly visible and stay in place. Include job name, address, phone numbers, and contact information.
- Secure panels on pallets with stretch wrap or metal bands. You will need a pallet jack and perhaps a forklift (depending on dock) to move the loaded pallets.
- Material must be packaged so that pallets remain stable. All panels must be straight on pallets and secured within the trailer so that there is no risk of loads falling during transit or unloading.

Not Acceptable For Recycling

- Panels from an installation where hazardous materials have been used
 - Foil-laminate panels
 - Fabric-faced laminate panels
 - Vinyl-faced laminate panels
 - Wet, moldy, or weathered ceiling panels
 - Wood fiber ceiling panels
 - Colored or post-painted panels
 - Non-USG manufactured ceiling tiles
 - Panels installed or manufactured prior to 1981 (unless verified and approved by USG)
-

Fold here and insert top flap between 2 pallets

USG Ceiling Panel Recycling Program



Pallet Packing Label

Product ID

Project Name

Address

City

State

Zip

ID Letter

(A,B,C, etc.)

Must Match
Samples Sent

This material had been loaded in accordance with USG's Recycling Program Agreement

Signature of USG Sales Associate or Contractor

of

denotes total number of loads returning to plant.