

USG BORAL SHEETROCK® ALL PURPOSE JOINT COMPOUND

SHEETROCK® ALL PURPOSE JOINT COMPOUND provides overall high performance, as well as superior working qualities and good open time. It offers excellent bond over bead, trim and fastener concealments.

This special latex formulation is ideal for embedding paper tape and for filling, leveling and finishing over gypsum panel joints, fasteners, bead and trim. Complies with ASTM C 475 (where applicable).

ALL PURPOSE JOINT COMPOUND

PRODUCT FEATURES



- Excellent bond
- Premium grade lightweight, all purpose or finishing compound
- May be used for all three coats or as a finishing coat
- Excellent workability, easy application by hand or with mechanical tools
- Minimal mixing and cleaning of tools
- Sandable by hand or with mechanical sanding tools
- Smooth finish
- Excellent surface for painting



1st Coat



2nd Coat



Finishing Coat



Sandable



Patching

RECOMMENDED

- Sheetrock All Purpose Joint Compound is suitable for use as all three coats in the USG Boral three coat jointing system
- Sheetrock All Purpose Joint Compound is suitable for the final coating of plasterboard joints, angles and fastener heads when used in conjunction with USG Boral setting type joint compounds for first and second coats

APPLICATION

- Surfaces must be clean and free from dust
- Sheetrock All Purpose Joint Compound may have high viscosity in the pail; it may be diluted to a workable viscosity by adding water followed by mechanical mixing
- Can be applied by hand or mechanical tools
- When using Sheetrock All Purpose Joint Compound paper tape must be used for taping in the first coat
- Finish all joints, externals and fasteners with a 3 coat system. Only 2 coat is required for internals

Directions - Jointing and Finishing

First Coat 150mm/300mm wide (Tapered Edge Joint/Square Edge Joint)

1. Cover joint with a thin layer of compound and embed paper tape, leaving at least 1mm of compound under the tape. Feather out the edges and allow to dry

Second Coat 200mm/400mm wide (Tapered Edge Joint/Square Edge Joint)

2. Lightly scrape back the joint before applying the second coat, feathering approximately 50mm (Tapered Edge Joint) or 100mm (Square Edge Joint) beyond the first coat. Allow to dry

Third Coat 250mm/500mm wide (Tapered Edge Joint/Square Edge Joint)

3. Lightly scrape back the joint and apply the third coat feathering 50mm (Tapered Edge Joint) or 100mm (Square Edge Joint) beyond the second coat. Allow to dry and sand lightly
4. Sheetrock All Purpose Joint Compound must be allowed to dry thoroughly (up to 24 hours depending on temperature and humidity) before re-coating or sanding
5. Only apply over setting type compounds that have been allowed to dry thoroughly
6. Sand with care using 180 or 220 grit paper. All surfaces including applied joint compound require light sanding, thoroughly dry, dust-free and not glossy before painting



7. Thoroughly clean all tools and equipment after use

NOTE: All surfaces including applied joint compound require light sanding before painting

MIXING

- Always use clean tools
- Do not mix with residues of previously used compounds
- The inclusion of such materials will impair the performance of this product and will void the product warranty
- Sheetrock All Purpose Joint Compound may appear thick in pail. Before adding water, lightly mix and test its application; if required, add water to achieve desired consistency
- **Caution:** Avoid over-thinning when adding water as this may cause cracking and excessive shrinkage
- If liquid has separated from the compound, stir carefully to restore consistency
- **Caution:** Do not overmix; overmixing can introduce air bubbles, which can create surface imperfections

STORAGE

- Sheetrock All Purpose Joint Compound should be stored under a cover in a dry environment and protected from temperature extremes; storage in an unsuitable environment can shorten the lifespan of this product
- Sheetrock All Purpose Joint Compound has a shelf life of 9 months from date of manufacture

PRODUCT INFORMATION

Colour	White
Drying Time	12-24 hours (depending on local conditions)
Packaging	Net 5kg and 28kg re-sealable pail
VOC	Meet ISO 11890-2 (<25g/L)
Jointing Coverage	Approximately 37.8L/100 sq.m (based on 3 coat jointing)
Skimming Coverage	33m ² (based on 1mm thickness)

LIMITATIONS

- The application of Sheetrock All Purpose Joint Compound at interior temperatures less than 10°C is not recommended. Under cold or wet weather conditions, allow more than 24 hours for thorough drying
- When diluting Sheetrock All Purpose Joint Compound do not vigorously over mix as this will introduce entrapped air which can result in surface imperfections
- Do not apply Sheetrock All Purpose Joint Compound over joints that are not thoroughly dry; pinholes may result
- Do not use sandpaper lower than 150 grit. Take care to avoid scratching when sanding
- The inclusion of other materials to a mix will impair the performance (e.g. reduced strength and poor adhesion) and void the product warranty
- Consume an opened bucket within 48 hours

PRECAUTIONARY STATEMENT

- Dust from this product contain silica. Prolonged inhalation may be harmful to health
- Ensure adequate ventilation. Wear eye protection and an approved disposable respirator
- If dust or paste causes irritation use impervious PVC, nitrile or rubber gloves. Wash exposed skin after handling. If product gets into the eyes, wash thoroughly with clean water
- Do not ingest contents of package. If ingested, seek medical advice immediately
- Keep contents out of reach of children
- Be conscious of the environment. Dispose of empty packaging in a responsible manner
- Follow safe lifting instructions on the product label

REFERENCES

For further health and safety instructions, refer to the Safety Data Sheet for this product, available from your USG Boral sales office or **USGBoral.com**

USG BORAL SDN. BHD. Reg. No.: 198501015361 (147816-U).

Lot 606, Jalan Lagoon Selatan, 47500 Subang Jaya, Selangor Darul Ehsan, Malaysia.

T (603) 5629 2000 F (603) 5629 2008 W USGBoral.com

