

USG BORAL COMPOUNDS

USG Boral manufactures and supplies an extensive range of high-quality and consistent joint compounds including bedding and base compounds, finishing, patching and skim compounds to transform your gypsum board joints, angles and fastener heads into one seamless surface.



PREMIUM JOINTING



PREMIUM PREMIX



PAPER TAPE

Description	USG Boral Premium Jointing is a plaster-based, all purpose compound especially designed for flush jointing gypsum board, internal/external angles and fastener heads	USG Boral Premium Premix is a lightweight, premixed, vinyl-based, air drying compound used for finishing gypsum board joints, internal/external angles, and fastener heads.	As a paper reinforcing tape, USG Boral Paper Tape is well famed for strengthening and fine-tuning the joints of interior drywall panels while preventing visible cracking.
Net Weight	20 kg	28 kg	-
Drying/Setting time	45 minutes (depending on local conditions)	12-24 hours (depending on local conditions)	-
Shelf life	9 months	9 months	-
Mixing ratio	1:2 (water to powder)	-	-
Dimension	-	-	50 mm x 75 m
Features	<p>EASE OF USE</p> <ul style="list-style-type: none"> • Easy to mix, and no lumps • Easy to apply under shear pressure • Fast drying time • Easy to sand <p>PERFORMANCE</p> <ul style="list-style-type: none"> • Excellent bond to paper tape or joint strength • Low shrinkage • High Coverage 		<ul style="list-style-type: none"> • High strength and resists tearing • No stretch and wrinkles • Superior center crease • Easier corner finish

* Note: The 9 month shelf life indicated for the products on this page applies if the products are stored strictly following USG Boral's storage instructions.



SHEETROCK® EASY COAT™



SHEETROCK® EASY SKIM™

Description	Sheetrock® Easy Coat™ is a plaster-based, setting type compound formulated for use over interior masonry, brick, block, concrete and pre-cast surfaces to level uneven walls. Easy Coat™ can be used in place of cement render.	Sheetrock® Easy Skim™ is a plaster-based setting type compound, designed for interior skim coating of multiple surfaces such as gypsum boards, masonry, concrete and pre-cast walls and ceilings.
Net weight	25 kg	25 kg
Mixing ratio	1:2 (water to powder)	1:2 (water to powder)
Working time	45 minutes	80 minutes
Setting time	80 minutes	120 minutes
Application thickness	5 mm to 50 mm	2 mm to 5 mm
Estimated coverage	4.08 sqm @ 5mm thick or 1.70 sqm @ 15mm thick	12.5 sqm @ 2mm thick
Shelf life	9 months	9 months
Features	<ul style="list-style-type: none"> • Strong bond for lasting quality • Formulated for a smooth finish that can be directly painted over • Designed to minimize cracks • Excellent coverage compared to cement render 	<ul style="list-style-type: none"> • Easy application over masonry, gypsum and precast wall • Fine smooth matte white finish • Excellent coverage



PREMIUM CORNICE



PREMIUM CASTING

Description	USG Boral Premium Cornice is a high-strength bonding compound formulated for adhering decorative cornices to walls and ceilings.	USG Boral Premium Casting is used mainly to cast plaster products such as cornices, corbels and other decorative moulding.
Net Weight	20 kg	20 kg
Setting time	30 minutes	10 minutes
Shelf life	9 months	9 months
Features	<ul style="list-style-type: none"> • High adhesion • Excellent wet tack • Smooth finish 	<ul style="list-style-type: none"> • Easy mixing • Consistent working time • Smooth pearly white finish

* Note: The 9 month shelf life indicated for the products on this page applies if the products are stored strictly following USG Boral's storage instructions.