



USG Boral Echostop

Submittal Sheet

USG Boral Echostop is a perforated gypsum board designed for systems requiring both superior acoustic and aesthetic qualities. It is recommended for use as wall or ceiling lining where sound absorption or decorative applications are required.



USG Boral Echostop

Submittal Sheet

Features and Benefits

- Simple Installation
- Flush Jointing
- Up to NRC of 0.75
- Green label certified

Application

- Large open ceiling areas
- Offices
- Schools
- Restaurants
- Shopping Malls
- Auditoriums
- Cinemas
- Hotels
- Concert Halls

Product Information

USG Boral Echostop S8 (S=Square Perforation, 8 sections)

S8		Size (mm)	12 x 1200 x 2400	Pattern	8 @ 22 x 22
		Weight (kg/m ²)	< 9.5 kg/m ²)	Perforation Rate (%)	13.4%
		Edge Shape	Tapered	Back Sound Paper	Ahlstrom 550
		Perforated Type	Square	Standard Packaging	40
		Perforated Size	10 x 10mm	NRC with 50mm SoundBlock	0.70

USG Boral Echostop R1 (R= Round Perforation, 1 section)

R1		Size (mm)	12 x 1200 x 2400	Pattern	1 @ 75 x 35
		Weight (kg/m ²)	< 9.5 kg/m ²)	Perforation Rate (%)	16.1%
		Edge Shape	Tapered	Back Sound Paper	Ahlstrom 550
		Perforated Type	Round	Standard Packaging	40
		Perforated Size	Ø 15mm	NRC with 50mm SoundBlock	0.75

USG Boral Echostop R2 (R= Round Perforation, 2 section)

R2		Size (mm)	12 x 1200 x 2400	Pattern	2 @ 42 x 42
		Weight (kg/m ²)	< 9.5 kg/m ²)	Perforation Rate (%)	13.8%
		Edge Shape	Tapered	Back Sound Paper	Ahlstrom 550
		Perforated Type	Round	Standard Packaging	40
		Perforated Size	Ø 12mm	NRC with 50mm SoundBlock	0.70

USG Boral Echostop R8 (R= Round Perforation, 8 section)

R8		Size (mm)	12 x 1200 x 2400	Pattern	8 @ 15 x 15
		Weight (kg/m ²)	< 9.5 kg/m ²)	Perforation Rate (%)	11.0%
		Edge Shape	Tapered	Back Sound Paper	Ahlstrom 550
		Perforated Type	Round	Standard Packaging	40
		Perforated Size	Ø 15mm	NRC with 50mm SoundBlock	0.60

The above specifications are standard plasterboard dimensions.

Suspension System Components

Suspension System Detail	No.	Item Number	Description
	1	Rondo P.N 129	Furring Channel @600mm C/C Max
	2	Rondo P.N 125	Top Cross Rail @ 1200mm C/C Max
	3	Rondo P.N 139	TCR Key Joiner (Adjustable)
	4	Rondo P.N 2534	TCR Clip and Rod Joiner
	5	Rondo P.N 121	Suspension Rod @1200mm C/C Max
	6	N/A	25mm USG Boral Plasterboard Screw
	7	N/A	Stagger Butt Points

For more information, please contact our technical service.

Australia
China
India
Indonesia
Malaysia
Middle East
New Zealand
Philippines
Singapore
South Korea
Thailand
Vietnam



041 - 001 - 2592
Environmentally Preferred
Product

USG BORAL PTE LTD

8 Boon Lay Way #02-06 TradeHub 21 Singapore 609964

Tel: (65) 6272 9272 Fax: (65) 6278 5310

Email: contact-us.sg@usgboral.com

USGBoral.com

USG BORAL 
INNOVATION INSPIRED BY YOU.™

The logo graphic consists of two overlapping triangles: a yellow one on top and a green one on the bottom, both pointing to the right.